SMART HOME **BUS**



SB-DALI-DN DALI Interface Bridge (48ch Broadcast)

.....

DIN-Rail Mount, Broadcast DALI Interface Bridge to interface to S-BUS for 3rd Party Integration. This Module is used for programming S.BUS, and a bridge To DALI network.

**Added function: Upgrade Port Ready, S-BUS Connector and S-Train Ready

technical data 🗔

Compatibility Broadcast DALI Ready



Channels 48 Channels/ Separated Areas

Upgrade IO 1 x mini USB port (to connect to special programming board)

Scenes

Built In Scenes Control
 On Power failure Scene Preset
Can be restored

User Controls

• LED status indicator

Diagnostic LED+ BROADCAST

Programming • Advanced Software Configuration & Programming **Operation Protection**

• BUS Rv. Polarity Protection • BUS Short Circuit Protection

Added IP functions

Remote management
 Intelligent data interchange to
 minimize the data flux

SBUS DC Supply

24VDC with flexible tolerance between 8-36VDC. Flexible ability to add power supply as to be needed any where Power consumption: 15mA

Installation

35mm DIN-Rail Mount Ready

• Wall Mount Ready (4P)

Operating Environment

0° to 45°C ambient temperature 20% to 93% RH



Compliance CE Mark EMC ROHs, CPT **Enclosure & Size** Polycarbonate, DIN-rail (4 Unit)

Dimensions & Weight W 91mm x L 73mm x H 75mm Packed weight 0.22 kg

3rd party compatibility 🤇



· HVAC · BMS

Motorized Curtains



GTIN (UPC-EAN): 0610696254979 Patent P. No: 201110123081.0 Patent No: 201120452441.7



