



SB-HotelSd-UN Smart Hotel Bedside Touch Panel

The touch panel is the Smart Hotel guest system command control equipment, has a high sensitivity capacitive touch sensor IC. Provides guest room three state service input, lighting control, scene control, curtain control, temperature control. Each touch button programmable target instruction count up to 20. Has mini USB firmware upgrade port.

LIGHTS MOOD CURTAIN CLIMATE SERVICE SMART HOTEL

technical data 👩 Touch Button Allocation

3 for Service Buttons 3 for Light Control Buttons **3 for Mood Control Buttons 3 for Curtain Control Buttons 3 for Climate Control Buttons**

Extra features

• Each button has a dual color LED for background and working status indication

· Auto sleep to reduce the current consumption when idle

• Easy sBUS connector tech.

Control Applications

lighting, HVAC, IR, moods and scenes, hotel guest room service

Compliance **CE Mark EMC**

Total Gangs

This Touch panel is equal to 20 gangs

Control IO

1 x Advanced RS485 S-BUS serial port links (both train & screw link types)

Upgrade IO

1 x mini USB port (to connect to special programming board)

Operation Protection

• BUS Rv. Polarity Protection

BUS Short Circuit Protection

SBUS DC Supply

24VDC with flexible tolerance between 8-32VDC. Flexible ability to add power supply as to be needed any where Power consumption: max 50mA

Installation

- wall Mount metal frame twist Magnetic screw less mount-
- ing
- Advanced security locking
- Easy sBUS connector tech.

Operating Environment

0° to 45°C ambient temperature 20% to 93% RH

Enclosure material Aluminum, Glass, and poly

Dimensions & Weight

L168mm x W100mm x H14.6mm; weight:0.23kg

control compatibility

commercial

GTIN (UPC-EAN): 0610696254825 Patent P. No:

• Lighting • Climate • Curtains • Moods • Service





SB-HotelSd-UN Smart Hotel BedSide Touch Panel

168

mounting dimensions 🚱

.

0



connection diagram

m

+24V D+D- GND

0000 S.BUS Connector

SERVICE

Haw

LIGHTS

All on

Read

ntch T

Si

00000

SERVICE LIGHTS MOOD CURTAIN CLIMATE Wake All on 20° Open Up Dress 23[°] Read Close Wasn Bed Stop Watch TV 26 Time SMART HOTEL \bigcirc \odot 85 12.4 S-BUS connection 🙆 CURTAIN CLMATE +24V D+D- GND Opei 20° 23° 0000 26° SMART HOTEL

PROSPECTIVE

MOOD

Wake Up


Close

Stop

Dress Wasn

8ed Time

比例 1:1



UTP core colors G4

S.BUS +24V

S.BUS GND

S.BUS D+

S.BUS D-

Spare +12v

Spare -12V

Spare

Spare

orange

blue

w/blue

green

w/green

W/brown

brown

w/orange

GROUP

www.smarthomebus.com • info@smarthomebus.com USA - Germany - Denmark - Hong Kong - Jordan - China - UAE

SB-G4 Data Sheet Rev 2.0 released Dec.2012

Specifications subject to change without notice. © Smarthome® -Group Trading as Smart-BUS®. Texas 77043 - USA. All rights reserved. Smart Mesh® , Smarthome BUS® and all other associated logos are the registered trademarks of Smart-Group® . Not to be used nor reproduced without written permission. All Patents and IPO's Remain owned by SmartHome® Group